

© (989) 358 6119 Sales@northamcon.com P.O. Box 454, Alpena, MI 49707 northamcon.com

FLAT MOTOR CONVEYOR WORKSHEET

Company		Date
		Desired Delivery
		State
NorthAmCon, Inc. Sales Contact		Quote #:
Quantity		
Product Specs: Max: - Width (inches): Length (inches): Height (inches): Weight (lbs): Min: - Width (inches): Length (inches): Height (inches): Weight (lbs):		Roller Specs: 1.9 in. dia. x 16 ga. Galv. Other: Coating: Support Type: Quantity: Legs Ceiling Supports TOR+/
Description:		3 - 1 - 3 - 1 - 1 - 1 - 1 - 1 - 1
Max. Qty.: Total Live Load: Temperature -Environment:Product:		Application Type: ☐ Transportation ☐ Zero Pressure - Zone Length
Conveyor Construction: Between Frame (BF) Roller C/C Roller Height: 1/4" high 1-3/4" loger frame in the second of the second	der Coat	TOR
Plant Voltage: ☐ 110V Single ☐ 220V Single Phase ☐ 460V Three Phase		
Speed: FPM VariabletoFPM		Notes:
Controls: Zone Photo Eye ☐ Yes Entry Zone Photo Eye ☐ Yes Power Distribution Cables ☐ Yes	□ No □ No □ No	

☐ Yes

Approval Drawing Required: \square Yes \square No

Power Supply

☐ No