

(989) 358 6119
 sales@northamcon.com
 P.O. Box 454, Alpena, MI 49707
 morthamcon.com

## **MOTORIZED ROLLER WORKSHEET**

| Company:  |                                   | Date:                      |  |
|---|-----------------------------------|----------------------------|--|
|   |                                   | Desired Delivery:          |  |
| Phone No.:  | _ Contact Email:                  |                            |  |
| NorthAmCon, Inc. Sales Contact:   |                                   | Quote #:                   |  |
| Part # of Rollers Currently Used:<br>Brand Preference:  |                                   |                            |  |
| Roller Specifications   | Application Information           |                            |  |
| Roller Quantity:  | Desired Spe                       | eed (FPM):                 |  |
| Roller Size: ☐ 1.9 OD x 7/16" Hex   |                                   | /eight (lbs):              |  |
| ☐ 2.5 OD x 11/16" Hex   |                                   | Transported Material Type: |  |
| Between Frame (inches) - A:   | Conveyor Type:                    |                            |  |
| Tube Length (inches) - B:   | Roller Center-to-Center (inches): |                            |  |
| Groove/Sprocket Location (inches) - C:  |                                   |                            |  |
| Groove/Sprocket Location (inches) - D:  | Motor Lead                        | (Cable) Length (inches):   |  |
| <ul> <li>☐ Plain</li> <li>☐ Grooved</li> <li>☐ Poly Ribbed</li> <li>☐ Sprocketed</li> <li>Retention</li> <li>☐ Spring Retained</li> </ul> | Card Function ☐ Trans             | ons Required:portation     |  |
| ☐ Other   | oposiai into                      |                            |  |

## **Brief Application Description**

(include extreme environmental and operating conditions, i.e. wet, oily, washdown, cold, hot, etc.): \_\_\_\_\_







